




USER MANUAL

Z5 1x26x28



MANUAL #VI SERIES
2026042101



READ IT BEFORE USE!!!

READ AND UNDERSTAND THE CONTENTS OF YOUR FIREARM'S AND SCOPE MANUAL. FOLLOW ALL STANDARD SAFETY PRECAUTIONS AND PROCEDURES DURING FIREARM OPERATION.



VICTOPTICS



Product Manual



FACEBOOK




INSTAGRAM



- NEVER LOOK AT THE SUN THROUGH THE SCOPE (OR ANY OTHER OPTICAL INSTRUMENT). IT MAY
 - PERMANENTLY DAMAGE YOUR EYES.
- MAKE SURE FIREARMS ARE UNLOADED AND POINTED IN THE SAFE DIRECTION.

PRODUCT FUNCTION DIAGRAM



1 Objective Lens

2 Windage

3 Elevation

4 Illumination Switch

5 Screws

6 Battery Compartment

7 Picatinny rail

MOUNTING

The red dot sight is installed on the gun by means of its integrated Picatinny mount. Place the sight objective lens towards the muzzle. Set the sight flat on top of the rail base. Make sure the cross bolt is located in a recoil groove. For safety reasons, allow at least 3 inches of clearance between the sight and your eyes.

ZEROING

The red dot sight features elevation and windage adjustments. Referring to the point of impact you will need to adjust both windage and elevation screws. The elevation is the vertical (up and down) adjustment, usually on the top of the sight. Windage is the horizontal (left-to-right) adjustment, usually on the right of the sight. With the sight is mounted aim at a target 25 yards away. Slowly shoot a small 3 to 5 round test group onto your target. Adjust windage & elevation screws in the direction you want to move the bullet impact. Should your impacts be below your point of aim, dial UP to reach zero.

ILLUMINATION

Press the illumination switch to activate the sight. Subsequently press the switch will change the dot intensity. The 1st level is the weakest and the 10th level is the brightest.

BATTERY EXCHANGE

Our red dot sight is powered by 1 piece of the CR2032 button battery. Should the dot grows dim or not turn on, you will need to exchange the battery. To exchange the CR2032 battery, release the two screws on the battery compartment tray. Pry the tray out, put or replace a new CR2032 battery. Push back the tray and fasten the screws.



Should the illumination grows dim or not turn on, you will need to exchange the battery.

MAINTENANCE

Your sight, though amazingly tough, is a precision instrument that deserves reasonable cautious care. Use lens covers whenever convenient.

- When cleaning the lens, first blow away any dirt and dust, or use a soft lens brush. Fingerprints and lubricants can be wiped off with lens tissue, or a soft clean cotton cloth, moistened with lens cleaning fluid.
- All moving parts of the sight are permanently lubricated. Do not try to lubricate them.
- No maintenance is needed on the sight outer surface, except to occasionally wipe off dirt or fingerprints with a soft cloth.
- Use lens covers whenever convenient.

STORAGE

Avoid storing the sight in hot places, such as the passenger compartments of vehicles on hot days. The high temperatures could adversely affect the lubricants and sealants. A vehicle's trunk, a gun cabinet, or a closet is preferable. Never leave the sight where direct sunlight can enter either the objective lens.

Damage may result from the concentration (burning glass effect) of the sun's rays.

RETICLE



3MOA

ONE YEAR WARRANTY

Your VictOptics product is warranted free of defects in materials and workmanship for a period of 1 year from the time of purchase by the original owner. In the event of a defect under this warranty, we will, at our option, repair or replace the product at no charge to you. If we can't repair your product, we will replace it with a product of equal or better physical condition.

This warranty does not cover damages caused by misuse, improper handling, loss, theft, deliberate damage, or cosmetic damage. The battery is not covered under this warranty. Also, this warranty is null and void if modification or maintenance is provided by someone other than VictOptics. This warranty is non-transferable.

For products not directly purchased from us, please contact the local dealer for applicable warranty information.

Any warranty must be registered and complete warranty terms must be followed by the link: [VICTOPTICS.COM/CONTACT-US](https://www.victpics.com/contact-us)